

# INSTALLATION AND USER MANUAL

**AIRSOFT SYSTEMS**

[www.airsoftsystems.com](http://www.airsoftsystems.com)



# ASCU3

With **Gen.3+** Technology

**ATTENTION!** PLEASE READ CAREFULLY THIS INSTRUCTION AND USER MANUAL BEFORE YOU PROCEED WITH THE INSTALLATION OF THE ASCU.

## **What is the ASCU-V3?**

The ASCU is a electronic module which when installed in an Airsoft Electric Gun, drastically improves the way the gearbox cycles and the realism in imitating the functions of a real weapon.

The ASCU monitors the actual position of the sector gear, the fire selector and the trigger. All the information is passed to the Electronic Control Unit, which analyzes it and controls the firing of the AEG by an active brake MOSFET.

The ASCU-V3 makes every standard AEG with Marui type of gearbox ver.3 to work exactly as the most expensive and sophisticated airsoft rifles on the market, like the professional class of training weapons.

The ASCU system monitors the operation of the AEG in any time, and no matter how fast you tap the trigger, the AEG will always complete the full cycle, no matter if you shoot in Semi or Full Auto mode. After each shot or burst the piston will stop in its foremost position.

With the installation of the ASCU, the Anti Reversal Latch (ARL), which is often a cause of gearbox jams, is no longer needed . (The ARL can remain in the AEG when a set-up of low power motor with low power spring, or High Speed motor with low power spring is used )

The ASCU has an integrated Low Drain Protection, which is specially designed to keep LiPo batteries from damage. LiPo, NiMH, and NiCd batteries from 7,4 V to 12 V can be used safely with the ASCU and there is no need to program or set up for the battery type used by any means. The ASCU automatically recognizes the battery type and voltage, even if the battery is not fully charged.

The ASCU will also stop the AEG firing if any mechanical problem occurs to the gears in the AEG, which protects the internals of the gearbox from further damage.

The ASCU-V3 is easy to install in all AEGs with Ver.3 gearbox (except AUG). In most of the models there is no need for any modification of the original parts of the airsoft rifle, nevertheless some models may need some minor and easy to do, modifications of some parts of the gearbox shells in order make the installation easier.

### **WARNING!**

Please read carefully this Instruction manual before proceeding with the installation. We strongly recommend that the ASCU to be installed by an experienced airsoft technician.

**IMPORTANT:** The ASCU works properly only with motors with strong magnets. With weak magnet motors the active brake will not be effective.

#### **The ASCU kit includes:**

- ECU board + Mosfet Board with Wires
- Selector Plate
- Improved Cut-Off Lever
- Heatsink syringe
- Instruction Manual

#### **Tools needed:**

- Super-Glue.

#### **Tools that may be needed:**

- Small file
- Dremel tool

## **ASCU INSTALLATION STEPS.**



**\*Before installation check on [www.airsoftsystems.com](http://www.airsoftsystems.com) for any updates!**

**WARNING!** If you are not familiar with the AEG's gearbox internals and you do not have good gearbox repair experience, please do not proceed with the installation and turn to your nearest airsoft service.


1. Remove the gearbox from your AEG by following the manufacturers procedures.
2. Open the gearbox and remove the cylinder together with the piston and the spring. Remove the gears and the anti-reversal latch and the selector plate. Unscrew the trigger switch assembly and remove it together with the wiring. (keep the screw, it is needed to hold the ASCU)

**Gearbox Maintenance Tip:** If your gearbox has a lot of grease inside and over the gears, clean it and lube the gears, and their axis with thin layer of silicone grease. Apply a thin layer of lubricant only to the contact surfaces. Over lubricating can result in drop of rate of firing and malfunction of the gearbox.



3. Insert the provided with your ASCU-V3 selector plate.




4. Remove the cut-off lever, and replace it with the polymer cut-off lever provided with your ASCU-V3. Replace the cut-off lever spring. Use the original screw.





5. Separate the ECU and the Mosfet of the ASCU. Pass the wires through the opening in the gearbox shell as shown on the picture.



6. In the place of the original switch group fix the Sensor Unit by screwing back the screw that was used for the original switch assembly.




7. Place over & connect the ASCU Mosfet to the ECU. **Be carefull to connect accurately the connecting pins of the ECU and Mosfet Boards.**



8. When connecting the two boards connect the pins EXACTLY as it is shown on the picture above.

9. Replace the gears. **Rotate by hand the sector gear and check if the cut-off lever is moving properly and if it activates the cut-off sensor lever. At the bottom position of the cut-off lever and the cut-off sensor, there must be a small gap between them.**



**WARNING! Do NOT reinstall the anti-reversal latch and the trigger safety lever! You do not need them anymore.**

**\*Anti-reversal latch may be reinstalled only if you use a low power magnets motor.**

10. Replace the cylinder together with the piston and the tappet plate. Reconnect the tappet plate spring. Replace the trigger with its spring.

11. With the provided Heat-sink syringe apply a drop of paste on top of the Mosfet transistors.

12. Insert the main spring and the spring guide. Close the gearbox.

13. Insert the gearbox in the AEG following the manufacturers instructions.

**WARNING! On some AEG models it may be needed to file or dremel some areas to make space to pass the stronger wires. Those wires have been chosen to guarantee maximum current flow in even the strongest AEG upgrades.**

**WARNING! If changing the Tamiya connector to Deans /T-connector/ make sure to keep the correct polarity. If the polarity is switched the ASCU will burn instantly and this will not be covered by the warranty.**

**Make sure to adjust the motor tension correctly.**

# **READ BEFORE USING YOUR AEG WITH ASCU!**

## **AIRSOFT SMART CONTROL UNIT USER MANUAL**

**The ASCU-3 has 7 selectable modes of function:**

1. Single fire + Combined 3 round Burst and Full Auto. (Factory setting)
2. Single Fire + Full Auto
3. Single Fire + 3 round Burst
4. Single Fire only.
- 5 AK Mode: Combined 3 round Burst and Full Auto +Semi
- 6 AK Mode: Full Auto +Semi
- 7 AK Mode: Single Fire + 3 round Burst

### **CHOOSING BETWEEN MODES:**

#### **Choosing Fire Mode:**

Set the fire selector to "Safe", then connect the battery, and within 3 seconds move the fire selector to "Full Auto" and pull the trigger. A long beep will indicate that you are now in "Program mode".

A Beep sequence will start: one beep for mode-1; two beeps for mode-2; and so on up to seven beeps for mode-7. Once you hear the number of beeps for the desired mode, pull the trigger and the mode will be selected. A single beep will indicate that the mode has been selected and the AEG is ready to operate.

The ASCU will remember the last chosen mode and will keep it until another mode is selected. Disconnecting of the battery does not affect the selected mode.

The ASCU is ready to work together with the ASHU with Empty Magazine Detecting function. The second program mode is used when the Hop-Up unit is installed in order to activate it. If you do not have the ASHU unit installed do not enter in this mode. The ASCU is factory preset to work without it.

If you have the ASHU installed then you need to enter in the second program mode to activate it.

\* You can order the ASHU from the same daeler from which you have ordered your ASCU.



## **Choosing Hop-Up Mode:**

Set the fire selector to "Safe", then connect the battery, and within 3 seconds move the fire selector to "Semi" and pull the trigger. A long beep will indicate that you are now in "Program mode".

A Beep sequence will start:

1. one beep for ASHU deactivation
2. two beeps for ASHU activation.
3. Three beeps for ASCU activation in automatic Bolt-Catch release mode.

After Choosing mode by pressing the trigger a long beep will indicate that the programing is over and the AEG is ready to be used.

The ASCU will remember the last chosen mode and will keep it until another mode is selected. Disconnecting of the battery does not affect the selected mode.

## **USING YOUR AEG WITH ASCU**

1. Connecting the Battery. After 3 seconds a single beep signal will indicate that the battery is connected and the AEG is ready for use.
2. When the fire selector lever is on "SAFE" the AEG will not fire when the trigger is pulled.
3. When the fire selector lever is on "SEMI" the AEG will fire a single shot each time the trigger is pulled.
4. When the fire selector lever is on "AUTO" and the trigger is pulled the AEG will fire fully automatic until the trigger is released, or 3 round burst ,or a single shot, dependent on which fire program mode the ASCU is set.
5. When the battery is depleted, the AEG will stop firing and you will hear a double beep signal. Change the battery with a charged one.

**Never leave your Airsoft Electric Gun with ASCU stored with the battery connected!  
Always disconnect the battery when the Airsoft gun is not used, stored or transported.  
Comply to all Airsoft Safety Rules at all times!**

## TEST MODE:

*This version of ASCU has a test mode, which is used to check the functionality of each component in case the ASCU is not working properly.*

1. To enter in this mode, take the ASCU out of the gearbox.
2. Then connect the both boards to each other and then connect the motor. (hold the motor tight in hand to prevent jumping on rotation).
3. Now connect the battery. Within 3 seconds push the lever of the cut-off sensor once. If you do this properly (and cut-off sensor works), you must hear 3 long beeps.

Now ASCU is in test mode and you can test its components:

4. Push the cut-off sensor: there must be a repeating beep while holding; (no beep means that sensor is not working)
5. Push the trigger switch on the Mosfet Board, the motor will start for a second and then stop. (no motor spinning means that trigger switch or selector switch is not working) After this you must push cut-off sensor again if you want to test fire again.
6. On the back of the ECU board you will find the fire-selector switch, hold the switch and press the trigger switch on the Mosfet Board, the motor will start and stop 2 times. (no motor spinning means that selector switch is not working) After this you must push cut-off sensor again if you want to test fire again.
7. Connect terminals of hop-up sensor connector with some kind of conductor and you have to hear a beep while holding; (no beep means that sensor is not working)

To exit of test mode just disconnect battery.

## TOUBLESHOOTING

The ASCU is designed to monitor the parameters in which your AEG works in. If by any reason mechanical or electrical failure the AEG does not work within the normal parameters, the ASCU will stop it and inform you for that with a double beep signal.

As there are a lot of AEG producers, and no matter that all of them are producing AEGs with gearboxes that are clones of the Tokyo Marui Ver-3, some times there are very small difference in dimensions and Stappes of some parts.

**For any other problems send your AEG to the nearest authorized service.**  
For complete list of authorized services check on [www.airsoftsystems.com](http://www.airsoftsystems.com)

**For updates and other information check on [www.airsoftsystems.com](http://www.airsoftsystems.com) and the technical support forum.**

Malfunction	Possible reason	What to do
When battery is connected there is no a beep signal.	Bad battery or AEG cable plug	Check the plugs.
	Bad or no connection of one of the wires with the motor	Check the motor connections with the black and red wires
	Short circuit of wires.	Check all wires. After the short-circuit is fixed the ASCU will resume normal function
When the fire selector is on "SEMI" or "AUTO" the AEG wont fire.	The trigger is not engaging the trigger switch.	Check the trigger and the trigger switch.
When the fire selector is on "SEMI" the AEG fires in auto.	Misplaced selector plate.	Check the selector assembly.
When the fire selector is on "SAFE" the AEG fires.	Misplaced selector	Check the selector assembly.
The AEG makes only few automatic shots and stops, no matter if the selector is on "SEMI" or on "AUTO"	The cutoff lever is not moving, or not installed properly, or broken.	Check the cutoff lever. If it is not moving freely ad lubricant if it is damaged - change it.
	The motor is overtightened.	Regulate the motor regulating screw
	The gears are overtightened.	Check the shimming.
	The motor is underpowered.	Change it with more powerful motor.
	The battery is damaged.	Check with another charged battery.
A broken or worn gear.		Change the gear.
The gears backspin after the shot.	Weak motor magnets.	Change the motor with one with stronger magnets.
		If there is no option to change the motor, install back the anti-reversal latch.
The wires get hot during firing	Loose connection to motor or battery.	Check all wire connections.
	Bad battery.	Change the battery.
	Bad Motor.	Change the motor.

# WARRANTY

The ASCU has a 12 months warranty for product defects. All ASCU with production defect will be replaced by Airsoft Systems.

## 2 YEARS EXTENDED WARRANTY:

**All ASCU kits that are instilled in our distributors service and have their warranty cards stamped by the service are receiving 1 extra year warranty.**

**WARRANTY VOID IF:** the ASCU is modified by the user, or any of its parts is damaged due to bad installation, bad handling, submerging in water, use with batteries with voltage higher than 12V, and damaged wires.

### RETURN AND REPLACEMENT:

All defective units must be returned to Airsoft Systems or their distributor in their original packing and warranty card. Replacement units will be returned within 45 days from the date they are received in Airsoft System's factory.

Airsoft Systems does not take any responsibility for delays and losses due to the post or courier services. Shipping back replacement units by mail / post service without insurance is free of charge. Shipping back replacement units by courier express service with insurance will be charged.

Owners name:

Date of instalation:

Authorized service  
signature and stamp:

**Airsoft Systems Ltd. is not taking any responsibility for damages, injuries and accidents resulting in the use of the ASCU or a Airsoft Electric Gun with installed ASCU.**