ASCU-M249 PROMark-II For M249 AEG gearboxes.

3 YEARS WORLDWIDE WARRANTY

INSTALLATION AND USER MANUAL

WARNING! Please read carefully this Instruction manual before proceeding with the installation. We strongly recommend that the ASCU to be installed by an experienced airsoft technican.

ASSUPRO! AIRSOFT SMART CONTROL UNIT

The ASCU PRO is designed with focus to provide the highest durability on the field, and simplicity of install and use.

We designed the PRO with the same approach as real-steel guns are build. So no Bluetooth and smartphones here! You can't connect a real-steel M4 or AK to a USB or smartphone - they are operated only by the safety lever and the trigger, so we did the same with the ASCU-PRO! You can set any of its functions on the field without even taking your gloves off.

The ASCU PRO is the smallest unit on the market, and it packs all functions that will give you the complete realism in functionality of your AEG replica.

Mark-II version is optimized for Brushless and classic motors.

Designed for M249 gearboxes.

- Single board control unit with processor and MOSFET
- Cycle detection with Active Brake- mechanical.
- Full Auto only / 3 rounds burst only/ Semi only.
- Safety: mechanical (provided with your AEG manufacturer)
- Short circuit protection: TSCP* (Total Short Circuit Protection)
- Maximum supply voltage: 15 V
- Max burst load: 240 A
- Battery compatibility: all DC batteries available up to 15V
- Battery connector: T-connector (new standard for airsoft)
- Wires 16 AWG with strong heat resistant PTFE insulation.


*TSCP will detect a short-circuit any time from the moment the battery is connected to the moment it is disconnected. The system checks for short-circuit: 1- on battery connection; 2- every time the trigger is pressed; 3-when motor spins. If short-circuit or overload is detected the system will immediately kill all processes and shut down the system. To reset the unit, the battery has to be disconnected and reconnected. ASCU will resume normal function once the short-circuit is fixed.

All ASCU boards are designed and manufactured in EU with strict quality control.


INSTALLATION STEPS

WARNING! If you are not familiar with the AEG's gearbox internals and you do not have good gearbox repair experience, please do not proceed with the installation and turn to your nearest airsoft service.


- 1. Remove the gearbox from your gun following the standard procedures for your model.
- 2. Open the gearbox and remove the cylinder together with the piston and the spring. Remove the gears, the anti-reversal latch and the trigger. Unscrew the switch assembly and remove it together with the wiring. Remove the cut-off lever.
- 3. At this point check the gearbox shell for any sharp edges in the way of the wires. If there are any, round them with a small file. Clean the gearbox shell from any dirt and grit. Check also the receiver for any sharp edges in the wires way, and if there are any, round them with a small file. All sharp edges in the wires way must be rounded because they can cut through the wires insulation.
- **4.** On the place of the original trigger switch place the ASCU and fasten it with the 2 screws provided with your ASCU.



5. Install back the sector gear. When installing it make sure to position it in a way that the cam under it faces up (12 o'clock) as shown on the picture.



6. Make sure that the sector gear is shimmed in a way that dos not touch the ASCU board, and there is a proper engagement of the cut-off switch.




- 7. To pass the wires through the opening of the gearbox shell before closing it there are 2 options:
- 1- Unsolder the T-Connector, pass through the wires and solder back the connector.

Make sure that you **DO NOT** switch the wires + & - when soldering back.

2- Cut a 3+ mm wide channel in the gearbox shell as shown on the picture. Make sure to smoothen any sharp edges with a file as they can damage the wires insulation.



- 8. Reinstall the Cyilinder / Piston group together eith the Nozzle, Tappet plate and spring.
- 9. Close the gearbox. Install Back the Main Spring and spring guide.





- !!! Make sure you connect properly to (+) of the motor to the RED wire and the (-) of the motor to the BLACK wire.
- !!! Make sure to adjust the motor tension correctly.

Connect the a battery to test the functionality of the AEG.

- ▶ Make sure motor height is optimal.
- ▶ Make sure the Safety works and no shot can be made when engaged.
- 10. On the pistol grip unit there is a bolt on the moving plunger. See the picture. Unscrew that bolt and with it attach the provided with your ASCU plastic extension. Make sure to attach it exactly as show on the picture, as ANY OTHER ORIENTATION WILL DAMAGE THE TRIGGER SWITCH.
- **11.** Check if the trigger is moving freely.
- **12.** Reinstall your gearbox and grip assembly back in your M249 AEG and go have fun!



READ BEFORE USING YOUR AEG WITH ASCU!

ASCU audio signals:

- 1 short signal AEG is ready for use.
- 1 long signal Battery deplated or overload.
- 2 long signals Short-circuit detected.

Choosing trigger mode for the Full Auto position:

- 1. Disconnect the battery
- 2. Connect the battery and pull the trigger all the way in before 3 seconds run out. The ASCU will make 4 fast short beeps to confirm that it is in Program Mode
- 3. The ASCU will emit a sequence of short beep signals:
 - 1 beep: Standard mode: 3-rnd burst at tap and full auto on hold.
 - 2 beeps: Full Auto.
 - 3 beeps: 3 round burst.
 - 4 beeps: Semi only.
- 4. After you hear the desired number, pull the trigger and the mode will be selected. A beep will confirm the selection and that the AEG is now ready for use.

TOUBLESHOOTING

The ASCU is designed to monitor the parameters in which your AEG works in. If by any reason mechanical or electrical failure the AEG does not work within the normal parameters, the ASCU will stop it and inform you for that with a double beep signal.

Malfunction	Possible reason	What to do
When battery is connected there is no a peep signal.	Bad battery or AEG cable plug	Check the plugs.
	Bad or no connection of one of the wires with the motor	Check the motor connections with the black and red wires
	Short circuit of wires.	Check all wires. After the short-circuit is fixed the ASCU will resume normal function
When the fire selector is on "SEMI" or "AUTO" the AEG wont fire.	The trigger is not reaching the	Check trigger installation.
	trigger switch or Broken trigger switch	Send to AS service.
The AEG makes only few automatic shots and stops, no matter if the selector is on "SEMI" or on "AUTO"	The sector gear cam is not acctivating the cutt-off switch	Check Sector gear shimming if it is not too high.
	or broken switch	Send to AS service.
The AEG stops firing with a double beep signal when the battery is charged	The motor is overtightened.	Regulate the motor regulating screw
	The gears are overtightened.	Check the shimming.
	The motor is underpowered.	Change it with more powerful motor.
	The battery is damaged.	Check with another charged battery.
	A broken or worn gear.	Change the gear.
The wires get hot during firing	Loose connection to motor or battery.	Check all wire connections.
	Bad battery.	Change the battery.
	Bad Motor.	Change the motor.

Technical support at: info@airsoftsystems.com

TEST MODE:

This version of ASCU has a test mode which can be used to diagnose if all of its components are working or there is a damaged component.

Can be used to check the Sector Gear to Cutt-off switch engagement during installation.

To enter in this mode you must have access to the Cutt-Off Switch on the ASCU:

To eneter in Test Mode:

- 1. Connect the wires to the motor. (hold the motor tight in hand to prevent jumping on rotation).
- 2. Now connect the battery. You have 3 seconds in which time you have to push the cut-off sensor once. If you do this properly (and cut-off sensor works), you must hear a 2 short beeps.

Now ASCU is in test mode and you can test its components:

- Push cut-off switch , you have to hear beep while holding; (no beep means that switch is not working)
- On the back of the ECU board you will find the fire-selector switch. Push the selector switch, you have to hear a beep. (no buzz sound means the switch is not working)
- Press the trigger switch, the motor will start spinning untill the trigger switch is released (no motor spinning means that trigger switch is not working).

To exit of test mode just disconnect battery. If you detect a problem with your ASCU please contact Airsoft Systems Support at support@airsoftsystems.com

WARRANTY

The ASCU has a 36 months warranty for product defects from the date of the purchaice. All ASCU with production defect will be replaced by Airsoft Systems.

Keep your invoice with as a proof of date of purchaice.

WARRANTY VOID IF the ASCU is modified by the user, or any of its parts are damaged due to improper use or bad installation.

RETURN AND REPLACEMENT:

All defective units must be returned to Airsoft Systems or their distributor toghether with the purchaice invoice.

Replacement units will be returned within 45 days from the date they are received in Airsoft Systems factory.

Airsoft Systems does not take any responsibility for delays and losses due to the post or courier services. Shipping back replacement units by mail / post service without insurance is free of charge. Shipping back replacement units by courier express service with insurance will be charged.

factory address:

AIRSOFT SYSTEMS LTD. 4 Iliensko Shose 1220 Sofia Bulgaria



DISCLAMER:

Manufacturer / distributor assumes no liability or responsibility of any injury, damage of any type, third party liability, diminished value or any other type of claim raised by the user, their collaterals, assigns and or agents of this product. By using this product the user accepts all personal and legal liability of any type listed under the UCC and all state regulatory agencies where applicable.

This Product is manufactured in Bulgaria (EU) by Airsoft Systems Ltd.

4 Iliensko Shose 1220 Sofia Bulgaria e-mail: Info@ airsoftsystems.com

